Renfert

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Revision date: 05/17/2023

die:master duo 1956 0600

Product code: 19560600 USA

Page 1 of 7

1. Identification

Product identifier

die:master duo 1956 0600

Further trade names

Further trade names		
1956 0800 die:master Set red		
1956 0900 die:master Set blue		
1956 1000 die:master Set gold/silv	/er	
1957 1000 die:master Set ivory		
1957 2000 die:master Set aqua		
Recommended use of the chemical and re	strictions on use	
Use of the substance/mixture		
Lacquer		
Uses advised against		
No information available.		
Details of the supplier of the safety data s	heet	
Manufacturer		
Company name:	Renfert GmbH	
Street:	Untere Giesswiesen 2	
Place:	D-78247 Hilzingen	
Telephone:	+49 7731 8208-0	
e-mail:	info@renfert.com	
Contact person:	Frau Andris	
e-mail:	silke.andris@renfert.com	
Internet:	www.renfert.com	
Supplier		
Company name:	Renfert USA	
Street:	3718 Illinois Avenue	
Place:	USA-60174 St. Charles IL	
Telephone:	(001) 800336-7422	
e-mail:	Bob@RenfertUSA.com	
Contact person:	Charlie Hagy	Telephone: +1 (630) 5497380
e-mail:	Charlie@RenfertUSA.com	
Internet:	www.renfert.com	
Emergency phone number:	USA: 800-222-1222 (National Poison Control number) 0	CA: British Columbia:
	800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414	or 944-1414 Saskatchewan:
	1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-80)0-268-9017 Quebec:
	1-800-463-5060 New Brunswick: 911 New Foundland: 1-	-866-727-1110 Northwest
	Territories: 1-800-332-1414 Nova Scotia: 1-800-565-816	1

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200 Flammable liquids: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2A Specific target organ toxicity single exposure: STOT SE 3 (narcotic effects)

Label elements

29 CFR Part 1910.1200

Signal word:





Hazard statements

Highly flammable liquid and vapor Causes serious eye irritation

May cause drowsiness or dizziness

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing vapours.

Wear protective gloves and eye/face protection.

Danger

Safety Data Sheet

according to 29 CFR 1910.1200(g)

die:master duo 1956 0600

Revision date: 05/17/2023

Product code: 19560600 USA

Page 2 of 7

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Hazards not otherwise classified

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

3. Composition/information on ingredients

Mixtures

Chemical characterization

Lacquer

Hazardous components

CAS No	Components	Quantity
78-93-3	butanone	< 75 %
123-86-4	n-butyl acetate	10 - 25 %

4. First-aid measures

Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

Get medical advice/attention if you feel unwell.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapors may cause drowsiness and dizziness. Process vapors can irritate airways,

skin and eyes. Repeated exposure may cause skin dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapors.

Special protective equipment and precautions for fire-fighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

Environmental precautions

Do not allow to enter into surface water or drains. Methods and material for containment and cleaning up



Safety Data Sheet

according to 29 CFR 1910.1200(g)

1956 0600

die:master duo

Revision date: 05/17/2023

Product code: 19560600 USA

Page 3 of 7

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Reference to other sections

Safe handling: see section 7 Personal protection equipment (PPE): see section 8 Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke when using this product.

Advice on protection against fire and explosion

Vapors may form explosive mixtures with air.

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Advice on general occupational hygiene

Avoid breathing vapours.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

8. Exposure controls/personal protection

Control parameters

Exposure limits

Substance	ppm	mg/m³	f/cc	Category	Origin
2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	PEL
2-Butanone	200	590		TWA (8 h)	REL
	300	885		STEL (15 min)	REL
n-Butyl acetate	150	710		TWA (8 h)	REL
	200	950		STEL (15 min)	REL
n-Butyl-acetate	150	710		TWA (8 h)	PEL
	2-Butanone (Methyl ethyl ketone) 2-Butanone n-Butyl acetate	2-Butanone (Methyl ethyl ketone) 2-Butanone 2-Butanone 1200 300 n-Butyl acetate 150 200	2-Butanone (Methyl ethyl ketone) 200 590 2-Butanone 200 590 300 885 300 885 n-Butyl acetate 150 710 200 950	2-Butanone (Methyl ethyl ketone) 200 590 2-Butanone 200 590 300 885 n-Butyl acetate 150 710 200 950 100	2-Butanone (Methyl ethyl ketone) 200 590 TWA (8 h) 2-Butanone 200 590 TWA (8 h) 300 885 STEL (15 min) n-Butyl acetate 150 710 TWA (8 h)

Exposure controls





Appropriate engineering controls

Safe handling: see section 7

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place

Renfert

Safety Data Sheet

Renfert Safety Data Sheet according to 29 CFR 1910.1200(g)					
	die:master duo	1956 0600			
Revision date: 05/17/2023			Page 4 of		
concontration and a	uantity of hazardous substances.		_		
Respiratory protection	uantity of hazardous substances.				
Use only in well-ven	tilated areas				
-	respirative protection necessary.				
Environmental exposur					
Do not allow to ente	r into surface water or drains.				
9. Physical and chemica	l properties				
Information on basic physic	cal and chemical properties				
Physical state:	Liquid				
Color:	colorless				
Odor:	characteristic				
			Test method		
Melting point/freezing po	int:	not determined			
Boiling point or initial boi	ling point and boiling	79 °C			
range:					
Lower explosion limits:		1,2 vol. %			
Upper explosion limits:		11,5 vol. %			
Flash point:		- 5 °C	DIN 51755 (cc)		
Auto-ignition temperature	e:	370 °C			
pH-Value:		not applicable			
Viscosity / kinematic:		not determined			
Water solubility:		Immiscible			
Partition coefficient n-oc	tanol/water:	not determined			
Vapor pressure:		105 hPa			
(at 20 °C)					
Density (at 20 °C):		0,78 - 0,88 g/cm³			
Chemical stability The product is chem Possibility of hazardous rea In case of insufficien Conditions to avoid	ty plosive mixtures with air. nically stable under recommended conditions of	ly flammable mixtures may devel	op.		
Incompatible materials No special measure	s are necessary.	ignition sources. No smoking.			
Hazardous decomposition No known hazardou	<u>products</u> s decomposition products.				
11. Toxicological inform					
Information on toxicologica	Il effects				
Acute toxicity					
Based on available of Irritation and corrosivity	data, the classification criteria are not met. /				
Sensitizing effects Based on available o	ion: Based on available data, the classification o data, the classification criteria are not met.	criteria are not met.			
	c/toxic effects for reproduction data, the classification criteria are not met.				

Safety Data Sheet Renfert according to 29 CFR 1910.1200(g) die:master duo 1956 0600 Revision date: 05/17/2023 Product code: 19560600 USA Page 5 of 7 Specific target organ toxicity (STOT) - single exposure May cause drowsiness or dizziness (butanone) Specific target organ toxicity (STOT) - repeated exposure Based on available data, the classification criteria are not met. Carcinogenicity (OSHA): No ingredient of this mixture is listed. Carcinogenicity (IARC): No ingredient of this mixture is listed. Carcinogenicity (NTP): No ingredient of this mixture is listed. Aspiration hazard Based on available data, the classification criteria are not met. Information on other hazards Endocrine disrupting properties This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria. Further information The product has not been tested. The statement is derived from the properties of the single components. 12. Ecological information Persistence and degradability There are no data available on the mixture itself. **Bioaccumulative potential** No indication of bioaccumulation potential. Mobility in soil There are no data available on the mixture itself. Endocrine disrupting properties This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria. Other adverse effects No information available. Further information Do not allow uncontrolled discharge of product into the environment. The product has not been tested. The statement is derived from the properties of the single components. 13. Disposal considerations Waste treatment methods **Disposal recommendations** Dispose of waste according to applicable legislation. 14. Transport information U.S. DOT 49 CFR 172.101 UN 1263 UN number or ID number: Proper shipping name: Paint 3 Transport hazard class(es): Packing group: Ш Hazard label: 3 Marine transport (IMDG) UN 1263 UN number or ID number: PAINT UN proper shipping name: Transport hazard class(es): 3 Packing group: Ш

Hazard label:

Marine pollutant:

3

no

Renfert GmbH Safety Data Sheet Renfert according to 29 CFR 1910.1200(g) die:master duo 1956 0600 Revision date: 05/17/2023 Product code: 19560600 USA Page 6 of 7 Air transport (ICAO-TI/IATA-DGR) UN 1263 UN number or ID number: PAINT UN proper shipping name: Transport hazard class(es): 3 Packing group: Ш Hazard label: 3 Environmental hazards ENVIRONMENTALLY HAZARDOUS: No Special precautions for user Further information: see section 6.7.8 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable 15. Regulatory information **U.S. Regulations** National regulatory information SARA Section 304 CERCLA: Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg) Butyl acetate (123-86-4): Reportable quantity = 5,000 (2270) lbs. (kg) SARA Section 311/312 Hazards: Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard Butyl acetate (123-86-4): Fire hazard, Immediate (acute) health hazard Clean Air Act Section 112(b): Methyl ethyl ketone (78-93-3) State Regulations Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California) This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants: not applicable Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not applicable 16. Other information Hazardous Materials Information Label (HMIS) Health: 2 Flammability: 3 Physical Hazard: 1 Personal Protection: В Changes Revision date: 05/17/2023 **Revision No:** 1.3 Abs. 2, 4, 9, 12, 16 * Data changed compared with the previous version. Abbreviations and acronyms PBT: persistent and bioaccumulative and toxic vPvB: very persistent, very bioaccumulative CAS: Chemical Abstracts Service (division of the American Chemical Society) ATE: Acute Toxicity Estimate LD50: lethal dose, 50% LC50: lethal concentration, 50% ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)



Safety Data Sheet

according to 29 CFR 1910.1200(g)

die:master duo 1956 0600

Revision date: 05/17/2023

Product code: 19560600 USA

Page 7 of 7

IMDG: International Maritime Code for Dangerous Goods ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships VOC: volatile organic compound(s)

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)